



CPO Style																
Part Number	d	D	PITCH	WIDTH	Ball Compliment		Internal Clearance		L1	L0	CRNR	BRG WT.	Radial	Axial	Load Rating	
	Bore	OD			Ball QTY	BALL DIA	MIN	MAX	O/R ID	I/R OD	BRK	LBS	Max RPM	Max RPM	Radial LBS	Axial LBS
PAA10CLO	1.000	1.375	1.188	0.1875	21	3/32	0.0010	0.0016	1.235	1.141	0.02	0.03	21000	0	147	0
PAA15CLO	1.500	1.875	1.688	0.1875	29	3/32	0.0012	0.0018	1.735	1.641	0.02	0.04	14000	0	182	0
PAA17CLO	1.750	2.124	1.938	0.1875	33	3/32	0.0012	0.0024	1.985	1.891	0.02	0.05	12000	0	198	0
PA020CPO	2.000	2.500	2.250	0.2500	27	1/8	0.0012	0.0024	2.313	2.187	0.03	0.10	10500	0	320	0
PB020CPO	2.000	2.625	2.313	0.3125	23	5/32	0.0012	0.0024	2.391	2.234	0.05	0.16	10500	0	450	0
PA025CPO	2.500	3.000	2.750	0.2500	33	1/8	0.0012	0.0024	2.813	2.687	0.03	0.13	8400	0	365	0
PB025CPO	2.500	3.125	2.813	0.3125	28	5/32	0.0012	0.0024	2.891	2.734	0.05	0.19	8400	0	525	0
PA030CPO	3.000	3.500	3.250	0.2500	39	1/8	0.0012	0.0024	3.313	3.187	0.03	0.15	6000	0	410	0
PB030CPO	3.000	3.625	3.313	0.3125	33	5/32	0.0012	0.0024	3.391	3.234	0.05	0.24	7000	0	570	0
PA035CPO	3.500	4.000	3.750	0.2500	45	1/8	0.0016	0.0028	3.813	3.687	0.03	0.18	5142	0	450	0
PB035CPO	3.500	4.125	3.813	0.3125	38	5/32	0.0016	0.0028	3.891	3.734	0.05	0.27	5145	0	635	0
PA040CPO	4.000	4.500	4.250	0.2500	51	1/8	0.0016	0.0028	4.313	4.187	0.03	0.20	4500	0	490	0
PB040CPO	4.000	4.625	4.313	0.3125	43	5/32	0.0016	0.0028	4.391	4.234	0.05	0.30	4500	0	700	0
PC040CPO	4.000	4.750	4.375	0.3750	35	3/16	0.0016	0.0028	4.470	4.280	0.05	0.45	5275	0	860	0
PD040CPO	4.000	5.000	4.500	0.5000	27	1/4	0.0016	0.0028	4.626	4.374	0.07	0.78	5250	0	1350	0
PF040CPO	4.000	5.500	4.750	0.7500	19	3/8	0.0016	0.0028	4.938	4.562	0.09	1.90	5250	0	2600	0
PG040CPO	4.000	6.000	5.000	1.0000	15	1/2	0.0016	0.0028	5.251	4.749	0.09	3.60	5250	0	4450	0
PA042CPO	4.246	4.746	4.496	0.2500	54	1/8	0.0016	0.0028	4.560	4.433	0.03	0.21	4235	0	510	0