



XPO Styles

Part Number	Bore	d	D	PITCH	WIDTH	Ball Compliment		Internal Clearance		L1	L0	CRNR	BRG WT. LBS	Radial Max RPM	Axial Max RPM	Load Rating	
						Ball QTY	BALL DIA	MIN	MAX							O/R ID	I/R OD
PAA10XLO	1.000	1.375	1.1875	0.1875	21	3/32	0.0010	0.0015	1.235	1.141	0.02	0.03	4000	11000	147	367	
PAA15XLO	1.500	1.875	1.6875	0.1875	29	3/32	0.0012	0.0017	1.735	1.641	0.02	0.04	2666	7333	182	455	
PAA17XLO	1.750	2.124	1.9375	0.1875	33	3/32	0.0012	0.0022	1.985	1.891	0.02	0.05	2285	6285	198	496	
PA020XPO	2.000	2.500	2.2500	0.2500	27	1/8	0.0012	0.0022	2.313	2.187	0.03	0.10	2000	5500	320	793	
PB020XPO	2.000	2.625	2.3125	0.3125	23	5/32	0.0012	0.0022	2.391	2.234	0.05	0.16	2000	5000	450	1130	
PA025XPO	2.500	3.000	2.7500	0.2500	33	1/8	0.0012	0.0022	2.813	2.687	0.03	0.13	1600	4400	370	910	
PB025XPO	2.500	3.125	2.8125	0.3125	28	5/32	0.0012	0.0022	2.891	2.734	0.05	0.19	1600	4400	525	1295	
PA030XPO	3.000	3.500	3.2500	0.2500	39	1/8	0.0012	0.0022	3.313	3.187	0.03	0.15	1166	3300	410	1015	
PB030XPO	3.000	3.625	3.3125	0.3125	33	5/32	0.0012	0.0022	3.391	3.234	0.05	0.24	1350	3700	570	1400	
PA035XPO	3.500	4.000	3.7500	0.2500	45	1/8	0.0016	0.0026	3.813	3.687	0.03	0.18	1000	2857	450	1115	
PB035XPO	3.500	4.125	3.8125	0.3125	38	5/32	0.0016	0.0026	3.891	3.734	0.05	0.27	1000	2900	635	1575	
PA040XPO	4.000	4.500	4.2500	0.2500	51	1/8	0.0016	0.0026	4.313	4.187	0.03	0.20	890	2500	490	1215	
PB040XPO	4.000	4.625	4.3125	0.3125	43	5/32	0.0016	0.0026	4.391	4.234	0.05	0.30	875	2600	700	1700	
PC040XPO	4.000	4.750	4.3750	0.3750	35	3/16	0.0016	0.0026	4.470	4.280	0.05	0.45	1000	2750	860	2130	
PD040XPO	4.000	5.000	4.500	0.500	27	1/4	0.0016	0.0026	4.626	4.374	0.07	0.78	1000	2750	1350	3350	
PF040XPO	4.000	5.500	4.750	0.750	19	3/8	0.0016	0.0026	4.938	4.562	0.09	1.90	1000	2650	2600	6500	
PG040XPO	4.000	6.000	5.000	1.000	15	1/2	0.0016	0.0026	5.251	4.749	0.09	3.60	1000	2700	4450	11100	
PA042XPO	4.246	4.746	4.4962	0.2500	54	1/8	0.0016	0.0026	4.560	4.433	0.03	0.21	830	2360	510	1260	
PB042XPO	4.246	4.871	4.5587	0.3125	45	5/32	0.0016	0.0026	4.638	4.480	0.05	0.31	850	2400	705	1750	
PC042XPO	4.246	4.996	4.6212	0.3750	37	3/16	0.0016	0.0026	4.716	4.527	0.05	0.47	825	2350	900	2270	
PD042XPO	4.246	5.246	4.746	0.500	28	1/4	0.0016	0.0026	4.872	4.620	0.07	0.83	950	2525	1400	3500	
PF042XPO	4.246	5.746	4.996	0.750	20	3/8	0.0016	0.0026	5.185	4.808	0.09	2.00	925	2550	2700	6700	
PG042XPO	4.246	6.246	5.246	1.000	15	1/2	0.0016	0.0026	5.497	4.995	0.09	3.80	925	2500	4450	11350	
PA045XPO	4.500	5.000	4.7500	0.2500	57	1/8	0.0016	0.0026	4.813	4.687	0.03	0.23	780	2230	525	1310	
PB045XPO	4.500	5.125	4.8125	0.3125	48	5/32	0.0016	0.0026	4.891	4.734	0.05	0.33	800	2300	740	1820	
PC045XPO	4.500	5.250	4.8750	0.3750	39	3/16	0.0016	0.0026	4.970	4.780	0.05	0.48	780	2230	910	2310	
PD045XPO	4.500	5.500	5.000	0.500	30	1/4	0.0016	0.0026	5.126	4.874	0.07	0.88	890	2420	1450	3600	