

## RJMX and RRSMX HEAVY DUTY; EXTRA HEAVY DUTY









RJMX - HEAVY DUTY

|          | WI DOTT             |        |        |            |            |              |         |         |            |                 | ULT.<br>STATIC |                   |
|----------|---------------------|--------|--------|------------|------------|--------------|---------|---------|------------|-----------------|----------------|-------------------|
|          | BORE X THD.<br>SIZE | B DIA. | D DIA. | W<br>WIDTH | T<br>WIDTH | BALL<br>DIA. | AM LGTH | N THD.  | CM<br>LGTH | a° MIS.<br>ANG. | RADIAL<br>LOAD | APPROX.<br>WEIGHT |
|          |                     | +.0015 |        | +.000      |            |              |         | UNF     | +.062      |                 |                |                   |
| PIBS P/N | REF.                | 0005   | +/010  | 005        | +/005      | REF.         | +/015   | 3A      | 031        | REF.            | LBS.           | LBS.              |
| RJMX 3   | 3/16 X 10-32        | 0.1900 | 0.625  | 0.312      | 0.250      | 0.437        | 1.125   | 10-32   | 0.750      | 13              | 2,851          | 0.028             |
| RJMX 4   | 1/4 X 1/4-28        | 0.2500 | 0.750  | 0.375      | 0.281      | 0.500        | 1.562   | 1/4-28  | 1.000      | 16              | 5,260          | 0.043             |
| RJMX 5   | 5/16 X 5/16-24      | 0.3125 | 0.875  | 0.437      | 0.344      | 0.625        | 1.875   | 5/16-24 | 1.250      | 14              | 7,125          | 0.072             |
| RJMX 6   | 3/8 X 3/8-24        | 0.3750 | 1.000  | 0.500      | 0.406      | 0.719        | 1.938   | 3/8-24  | 1.250      | 12              | 8,939          | 0.112             |
| RJMX 7   | 7/16 X 7/16-20      | 0.4375 | 1.125  | 0.562      | 0.437      | 0.812        | 2.125   | 7/16-20 | 1.375      | 14              | 9653           | 0.160             |
| RJMX 8   | 1/2 X 1/2-20        | 0.5000 | 1.312  | 0.625      | 0.500      | 0.937        | 2.438   | 1/2-20  | 1.500      | 12              | 15500          | 0.249             |
| RJMX 10  | 5/8 X 5/8-18        | 0.6250 | 1.500  | 0.750      | 0.562      | 1.125        | 2.625   | 5/8-18  | 1.625      | 16              | 17148          | 0.382             |
| ALJM 12  | 3/4 X 3/4-16        | 0.7500 | 1.750  | 0.875      | 0.687      | 1.312        | 2.875   | 3/4-16  | 1.750      | 14              | 27,021         | 0.602             |

RRSMX - EXTRA HEAVY DUTY

|          | BORE X THD.   | B DIA. | D DIA. | W<br>WIDTH | T<br>WIDTH | BALL<br>DIA. | AM LGTH | N THD.  | CM<br>LGTH | a° MIS.<br>ANG. | ULT.<br>STATIC<br>RADIAL<br>LOAD | APPROX.<br>WEIGHT |
|----------|---------------|--------|--------|------------|------------|--------------|---------|---------|------------|-----------------|----------------------------------|-------------------|
|          |               | +.0015 |        | +.000      |            |              |         | UNF     | +.062      |                 |                                  |                   |
| PIBS P/N | REF.          | 0005   | +/010  | 005        | +/005      | REF.         | +/015   | 3A      | 031        | REF.            | LBS.                             | LBS.              |
| RRSMX 3  | 3/16 X 1/4-28 | 0.1900 | 0.750  | 0.312      | 0.250      | 0.437        | 1.562   | ;1/4-28 | 1.000      | 10              | 5,260                            | 0.043             |
| RRSMX 4  | 1/4 X 5/16-24 | 0.2500 | 0.875  | 0.375      | 0.281      | 0.500        | 1.875   | 5/16-24 | 1.250      | 13              | 8,452                            | 0.072             |
| RRSMX 5  | 5/16 X 3/8-24 | 0.3125 | 1.000  | 0.437      | 0.344      | 0.625        | 1.938   | 3/8-24  | 1.250      | 12              | 12,978                           | 0.112             |
| RRSMX 6  | 3/8 X 7/16-20 | 0.3750 | 1.125  | 0.500      | 0.406      | 0.719        | 2.125   | 7/16-20 | 1.375      | 10              | 17,508                           | 0.160             |
| RRSMX 7  | 7/16 X 1/2-20 | 0.4375 | 1.312  | 0.562      | 0.437      | 0.812        | 2.438   | 1/2-20  | 1.500      | 12              | 22,760                           | 0.249             |
| ALRSM 8  | 1/2 X 5/8-18  | 0.5000 | 1.500  | 0.625      | 0.500      | 0.937        | 2.625   | 5/8-18  | 1.625      | 10              | 30,579                           | 0.382             |
| ALRSM 10 | 5/8 X 3/4-16  | 0.6250 | 1.750  | 0.750      | 0.562      | 1.125        | 2.875   | 3/4-16  | 1.750      | 13              | 39.674                           | 0.602             |