		Ø 28 (D)		Ø 12 (d)		
Closure	Metallic Shield					
Ring Material	52100 Chrome Steel		2	~~~		
Ball Material	52100 Chrome Steel			ות		
Precision	Abec 1					
Radial Clearance	Clearance C3					
Lubrication L627 Polyrex EM Grease						
Dynamic Load Capacity (Cr):	1146.53 lbs					
Static Load Capacity (Cor):	537.29 lbs					
Max Speed Grease	26000 rpm					
Max Speed Oil	30000 rpm		COMPONENT	METRIC SERIES	SHIELD	
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	6001–ZZ–C3/L627 TPI BRAND 12 mm x 28 mm x 8 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Metal Shields		UNIT	
					mm	
					SHEET	