		Ø 35 (D)		Ø 17 (d)	
Closure	Metallic Shield				
Ring Material	52100 Chrome Steel		-2_	<u>_</u> C-	
Ball Material	52100 Chrome Steel			ונ	
Precision	Abec 1				
Radial Clearance C3					
Lubrication L627 Polyrex EM Grease					
Dynamic Load Capacity (Cr):	1528.70 lbs				
Static Load Capacity (Cor):	753.11 lbs				
Max Speed Grease	20000 rpm				
Max Speed Oil	24000 rpm		COMPONENT	METRIC SERIES	SHIELD
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	6003–ZZ–C3/L627 TPI BRAND 17 mm x 35 mm x 10 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Metal Shields		UNIT mm
					SHEET