N N N I I H	TPI	Ø 32 (D)			
Closure	Rubber Seal Non-Contact			<u>A</u>	
Ring Material 52100 Chrome Steel					
Ball Material 52100 Chrome Steel					
Precision Abec 1					
Radial Clearance C3					
Lubrication	L627 Polyrex EM Grease				
Dynamic Load Capacity (Cr):	1371.34 lbs	1		SPECIAL BORE	SERIES
Static Load Capacity (Cor):	618.22 lbs		COMPONENT	NON-CONTAC	
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose. of the file. information or	6201-LLB-C3/L627-1/2 TPI .5000 in x 32 mm x 10 mm,		UNIT
					mm
	ww.pibsales.store	any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	Single Row Radial, Deep Groove Ball Ball Bearing, Two Non-Contact Rubber Seals		SHEET