N H M H	TPI	Ø 40 (D)		2) Ø .5000 (d) (d)	
Closure	Rubber Seal Non-Contact			<u>AU</u>	
Ring Material 52100 Chrome Steel					
Ball Material 52100 Chrome Steel		_			
Precision Abec 1					
Radial Clearance C3					
Lubrication	L627 Polyrex EM Grease	-		i	
Dynamic Load Capacity (Cr): Static Load Capacity (Cor):	2158.17 lbs 1034.12 lbs		COMPONENT	SPECIAL BORE NON-CONTAC	
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	6203–LLB–C3/L627–1/2 TPI .5000 in x 40 mm x 12 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Non-Contact Rubber Seals		UNIT mm
					SHEET