



Closure	Rubber Seal Non-Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	Abec 1
Radial Clearance	C3
Lubrication	L627 Polyrex EM Grease
Dynamic Load Capacity (Cr):	2877.55 lbs
Static Load Capacity (Cor):	1494.98 lbs
Max Speed Grease	16000 rpm
Max Speed Oil	18000 rpm

COMPONENT	METRIC SERIES NON-CONTACT SEAL
-----------	-----------------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

6204-LLB-C3/L627 TPI BRAND 20 mm x 47 mm x 14 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Non-Contact Rubber Seals	UNIT
	mm
	SHEET