		Ø 72 (D)		Ø 35 (d)	
Closure Ring Material	Metallic Shield 52100 Chrome Steel				
Ball Material	52100 Chrome Steel				
Precision	Abec 1		ШЦ	2	
Radial Clearance	C3	·			
Lubrication		· · · · · · · · · · · · · · · · · · ·			
Dynamic Load Capacity (Cr):	5777.59 lbs				
Static Load Capacity (Cor):	3439.58 lbs				
Max Speed Grease	9800 rpm				
Max Speed Oil	11000 rpm		COMPONENT	METRIC SERIES	SHIELD
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	6207–ZZ C3 TPI BRAND 35 mm x 72 mm x 17 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Metal Shields		UNIT
					mm
					SHEET