



Closure	Rubber Seal Non-Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	Abec 3
Radial Clearance	Normal
Lubrication	L038 Mobil Polyrex EM Grease
Dynamic Load Capacity (Cr):	8205.53 lbs
Static Load Capacity (Cor):	5395.41 lbs
Max Speed Grease	4800 nG

COMPONENT	METRIC SERIES SEAL	
<b>6210-2RSR</b> <b>FAG BRAND</b> 50mm x 90mm x 20mm, Single Row Radial, Deep Groove Bearing, Two Non Contact Rubber Seals	UNIT	
	mm	
	SHEET	



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)  
[www.pibsales.store](http://www.pibsales.store)

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.