



| | |
|-----------------------------|---------------------------|
| Closure | Rubber Seal Contact |
| Ring Material | 52100 Chrome Steel |
| Ball Material | 52100 Chrome Steel |
| Precision | Abec 1 |
| Radial Clearance | Normal |
| Lubrication | L627 Polyrex EM Grease |
| Dynamic Load Capacity (Cr): | 3574.46 lbs |
| Static Load Capacity (Cor): | 1775.99 lbs |
| Max Speed Grease | 10000 rpm |
| Note | Dust/Water Resistant Seal |

| COMPONENT | METRIC SERIES CONTACT SEAL |
|---|----------------------------|
| 6304-LLU/L627 TPI BRAND 20 mm x 52 mm x 15 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Contact Rubber Seals | UNIT |
| | mm |
| | SHEET |



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.