		Ø 22 (D)		Ø 10 (d)	
Closure	Rubber Seal Contact			<u> </u>	
Ring Material	52100 Chrome Steel		a		
Ball Material	52100 Chrome Steel			<u>۲</u>	
Precision	Abec 1			FG	
Radial Clearance	C3	↓ <b>↓</b>			
Lubrication					
Dynamic Load Capacity (Cr):	606.98 lbs				
Static Load Capacity (Cor):	285.51 lbs				
Max Speed Grease	21000 rpm			METRIC SE	
Note	Dust/Water Resistant Seal		COMPONENT	CONTACT S	
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	TPI BRAND mm   10 mm x 22 mm x 6 mm, mm   Single Row Radial, Deep Groove Ball Ball Image: Content of the second		UNIT
					mm
					SHEET