







Ø 50 Ø 65 (d) (D)

s...1)

ACB, CB

719..ACE, 719..CE

70..ACE, 70..CE

Contact Angle	15° High-Capacity Design
Bearing Arrangement	Pair - Universal Matched
Precision	P4
Ring Material	Chrome Steel 100Cr6
Ball Material	Chrome Steel 100Cr6
Preload	Light Preload
Dynamic Load Capacity(Cr)	1665.83 lbs
Static Load Capacity (C0r)	1753.52 lbs
Speed Rating Grease	20,000 rpm
Speed Rating Oil	30,000 rpm

ACD, CD

COMPONENT

SUPER PRECISION ANGULAR CONTACT



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

71810 CD/P4ADGA SKF

50 mm x 65 mm x 7 mm, Angular Contact Bearing, 15° Contact Angle, Pair - Universal Matched UNIT

mm

SHEET