



| | |
|-----------------------------|---------------------------|
| Closure | Metallic Shield |
| Ring Material | AISI 440C Stainless Steel |
| Ball Material | AISI 440C Stainless Steel |
| Precision | ABEC 3 |
| Radial Clearance | P25 (Standard) |
| Lubrication | LY308 |
| Dynamic Load Capacity (Cr): | 112 lbs |
| Static Load Capacity (Cor): | 46 lbs |
| Max Speed Grease x 1000 rpm | 60 |
| Max Speed Oil x 1000 rpm | 71 |
| Ball Compliment No. Z | 10 |
| Ball Compliment Size Dw | 3/64 |

| | |
|-----------|------------------------|
| COMPONENT | METRIC SERIES SHIELDED |
|-----------|------------------------|



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

| | |
|---|-------|
| DDL-950ZZHA3P25LY308 NMB BRAND 5 mm x 9 mm x 3 mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields | UNIT |
| | mm |
| | SHEET |