



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 5
Radial Clearance	P25 (Standard)
Lubrication	LY69 Grease
Dynamic Load Capacity (Cr):	243 lbs
Static Load Capacity (Cor):	95 lbs
Max Speed Grease x 1000 rpm	50
Max Speed Oil x 1000 rpm	59
Ball Compliment No. Z	8
Ball Compliment Size Dw	2.0 mm

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDR-1350ZZRA5P25LY69
NMB BRAND
 5mm x 13mm x 4mm, Miniature
 Instrument Deep, Groove Radial Ball
 Bearing, Two Metal Shields

UNIT
mm
SHEET