



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	504 lbs
Static Load Capacity (Cor):	205 lbs
Max Speed Grease x 1000 rpm	38
Max Speed Oil x 1000 rpm	45
Ball Compliment No. Z	6
Ball Compliment Size Dw	3,5

COMPONENT	METRIC SERIES SHIELDED	
DDR-1970ZZRA1P25L01 NMB BRAND 7.0 mm x 19.0 mm x 6.0 mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields	UNIT	
	mm	
	SHEET	



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com
www.pibsales.store

This file and any associated information
 and specifications are provided for
 reference and evaluation purposes only,
 and is subject to change without notice.
 PIB makes no representations, warranties
 or guarantees as to the appropriateness,
 accuracy, completeness, or suitability for
 any purpose, of the file, information or
 specifications. You are solely responsible
 for the use of the file, information or
 specifications.