



| | |
|-----------------------------|------------------------------|
| Closure | Metallic Shield |
| Ring Material | AISI 440C Stainless Steel |
| Ball Material | AISI 440C Stainless Steel |
| Precision | ABEC 3 |
| Radial Clearance | P25 (Standard) |
| Lubrication | LY121 Kyodo Yushi SRL Grease |
| Dynamic Load Capacity (Cr): | 146 lbs |
| Static Load Capacity (Cor): | 51 lbs |
| Max Speed Grease x 1000 rpm | 66 |
| Max Speed Oil x 1000 rpm | 78 |
| Ball Compliment No. Z | 7 |
| Ball Compliment Size Dw | 1/16 |

| COMPONENT | INCH SERIES SHIELDED | |
|--|----------------------|--|
| DDR-2ZZ R A3P25LY121 NMB BRAND .1250in x .3750in x .1562in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields | UNIT | |
| | INCH | |
| | SHEET | |



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com
www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.