



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 3
Radial Clearance	P25 (Standard)
Lubrication	LG39 Exxon Andok C Grease
Dynamic Load Capacity (Cr):	390 lbs
Static Load Capacity (Cor):	152 lbs
Max Speed Grease x 1000 rpm	46
Max Speed Oil x 1000 rpm	54
Ball Compliment No. Z	7
Ball Compliment Size Dw	7/64

COMPONENT	METRIC SERIES SHIELDED
-----------	------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDR1640ZZRA3P25LG39 NMB BRAND 4mm x 16mm x 5mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields	UNIT
	mm
	SHEET