



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	85 lbs
Static Load Capacity (Cor):	28 lbs
Max Speed Grease x 1000 rpm	76
Max Speed Oil x 1000 rpm	90
Ball Compliment No. Z	7
Ball Compliment Size Dw	1.2
Flanged	Flanged

COMPONENT	METRIC SERIES SHIELDED FLANGED	
<b>DDRF-720ZZRA1P25L01</b> <b>NMB BRAND</b> 2.0 mm x 7.0 mm x 3.5 mm, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields	UNIT	
	mm	
	SHEET	



Pacific International Bearing, Inc.  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)  
[www.pibsales.store](http://www.pibsales.store)

This file and any associated information  
 and specifications are provided for  
 reference and evaluation purposes only,  
 and is subject to change without notice.  
 PIB makes no representations, warranties  
 or guarantees as to the appropriateness,  
 accuracy, completeness, or suitability for  
 any purpose, of the file, information or  
 specifications. You are solely responsible  
 for the use of the file, information or  
 specifications.