


Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	271 lbs
Static Load Capacity (Cor):	201 lbs
Max Speed Grease x 1000 rpm	
Max Speed Oil x 1000 rpm	
Ball Compliment No. Z	
Ball Compliment Size Dw	



COMPONENT

INCH SERIES SHIELDED



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDRI-1634ZZRA1P25L01 NMB BRAND

.7500 in x 1.0000 in x .1562 in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields UNIT

INCH

SHEET