



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	127 lbs
Static Load Capacity (Cor):	41 lbs
Max Speed Grease x 1000 rpm	70
Max Speed Oil x 1000 rpm	82
Ball Compliment No. Z	6
Ball Compliment Size Dw	1.588
Flanged	Flanged

COMPONENT	INCH SERIES SHIELDED FLANGED	
DDRIF-518ZZRA1P25L01 NMB BRAND .1250 in x .3125 in x .1406 in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields	UNIT	
	INCH	
	SHEET	



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.