



Closure	Metallic Shield
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 1
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	88 lbs
Static Load Capacity (Cor):	32 lbs
Max Speed Grease x 1000 rpm	64
Max Speed Oil x 1000 rpm	76
Ball Compliment No. Z	10
Ball Compliment Size Dw	1
Flanged	Flanged

COMPONENT	INCH SERIES SHIELDED FLANGED
-----------	---------------------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDRIF-5532ZZRA1P25L01
NMB BRAND
 .1562 in x .3125 in x .1250 in,
 Miniature Instrument Deep, Groove Radial
 Ball Bearing, Two Metal Shields

UNIT
INCH
SHEET