


Closure	Rubber Seal Contact
Ring Material	AISI 440C Stainless Steel
Ball Material	AISI 440C Stainless Steel
Precision	ABEC 3
Radial Clearance	P25 (Standard)
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load Capacity (Cr):	84 lbs
Static Load Capacity (Cor):	40 lbs
Max Speed Grease x 1000 rpm	48
Max Speed Oil x 1000 rpm	56
Ball Compliment No. Z	10
Ball Compliment Size Dw	1/16



COMPONENT

INCH SERIES SEAL



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

DDRIF814ZZRA3P25Y121 NMB BRAND

.2500in x .5000in x .1875, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Contact Rubbers Seals UNIT

INCH

SHEET