		Ø 3.0000 (D)	0.6250 (A)	(SD)	0.2500 (F)
(D) Roller Diameter	3.0000 in			1.2500 (TL)	
(B) Roller Width	1.7500 in				
(SD) Stud Diameter	1.5000 in				
(SL) Stud Length	2.5000 in				
(TL) Thread Length	1.2500 in		500 2.500	0	
F	0.2500 in] (E	(B) (SL)		
Α	0.6250 in				
G	0.1870 in				
Speed Limit	1.600]			
Dynamic Capacity C(lbf)	17.000]			
Static Capacity C0 (lbf)	49.900]	COMPONENT	CAM FOLLO	WER
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com www.pibsales.store		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for	H96LW RBC 3in x 1.750in, Needle Roller Cam Follower, Heavy Duty Stud - Hex Head, Sealed - Hex Lube		UNIT Inch
		any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.			SHEET