



Closure	Rubber Seal Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	Abec 1
Radial Clearance	Normal
Lubrication	2A Alvania Grease S2
Dynamic Load Capacity (Cr):	741.87 lbs
Static Load Capacity (Cor):	314.73 lbs
Max Speed Grease	31000 rpm
Note	Dust/Water Resistant Seal

COMPONENT	R-SERIES INCH CONTACT SEAL	
<b>R6-LLU/2A</b> <b>TPI BRAND</b> 0.375 in x 0.875 in x 0.2812 in, Single Row Radial, Deep Groove Ball Ball Bearing, Two Contact Rubber Seals	UNIT	
	INCH	
	SHEET	



Pacific International Bearing, Inc.  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com  
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.