



| | |
|-----------------------------|-------------------------|
| Closure | Metallic Shield Pressed |
| Ring Material | 52100 Chrome Steel |
| Ball Material | 52100 Chrome Steel |
| Precision | ABEC 3 |
| Radial Clearance | P25 (Standard) |
| Lubrication | L01 Ester Oil |
| Dynamic Load Capacity (Cr): | 331 lbs |
| Static Load Capacity (Cor): | 134 lbs |
| Max Speed Grease x 1000 rpm | 42 |
| Max Speed Oil x 1000 rpm | 50 |
| Ball Compliment No. Z | 8 |
| Ball Compliment Size Dw | 3/32 |

| | |
|-----------|----------------------------|
| COMPONENT | INCH SERIES SHIELD FLANGED |
|-----------|----------------------------|



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

| | |
|--|-------|
| RF-4HHMT RA3 P25L01 NMB BRAND .2500in x .6250in. x .1960in, Miniature Instrument Deep, Groove Radial Ball Bearing, Non-Removable Metallic Shield | UNIT |
| | INCH |
| | SHEET |