


Closure	Metallic Shield
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	ABEC 3
Radial Clearance	P25 (Standard)
Lubrication	L01 Ester Oil
Dynamic Load Capacity (Cr):	331 lbs
Static Load Capacity (Cor):	134 lbs
Max Speed Grease x 1000 rpm	38
Max Speed Oil x 1000 rpm	45
Ball Compliment No. Z	6
Ball Compliment Size Dw	9/64



COMPONENT

INCH SERIES SHIELDED



Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com

www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

RI-1214ZZRA3 P25L01

NMB BRAND

.2500in x .7500in x .2812in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields UNIT

INCH

SHEET