



Closure	Metallic Shield Staked
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	ABEC 3
Radial Clearance	P25 (Standard)
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load Capacity (Cr):	747 lbs
Static Load Capacity (Cor):	313 lbs
Max Speed Grease x 1000 rpm	31
Max Speed Oil x 1000 rpm	37
Ball Compliment No. Z	7
Ball Compliment Size Dw	5/32

COMPONENT	INCH SERIES SHIELDED
-----------	----------------------



Pacific International Bearing, Inc.  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com  
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

<b>RI-1438KKRA3P25LY121</b> <b>NMB BRAND</b> .3750in x .8750in x .2188in, Miniature Instrument Deep, Groove Radial Ball Bearing, Non-Removable Metallic Shield	UNIT
	INCH
	SHEET