



| | |
|--------------------------|-----------|
| (D) Roller Diameter | 1.0000 in |
| (B) Roller Width | 0.6250 in |
| (SD) Stud Diameter | 0.4375 in |
| (SL) Stud Length | 1.0000 in |
| Speed Limit | 4.500 |
| Dynamic Capacity C (lbf) | 2.300 |
| Static Capacity C0 (lbf) | 4.800 |

| | |
|-----------|--------------|
| COMPONENT | CAM FOLLOWER |
|-----------|--------------|



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com
 www.pibsales.store

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

| | |
|--------------------------------------------------------------------------------------------------------------------|-------|
| S32LW RBC 1.0in x 0.6250in, Needle Roller Cam Follower, Standard Stud - Hex Head, Sealed | UNIT |
| | Inch |
| | SHEET |