



SINTERED AND SPHERICAL BEARINGS



Sintered and spherical bearings are available with:

- Oil cups or grease fittings
- Sintered or cast iron, bronze and nylon ball units

Expertly designed and manufactured, featuring:

- Self-aligning ball and socket design that compensates for surface or shaft mounting irregularities
- Self-metering lubrication system, including a factory-filled, large lubricant reservoir and capillary feeder system (grease fittings shipped dry)
- Precision bores supplied to customer specification, accurately sized and straightened to eliminate variations occurring in press-fitted parts

Triangle sintered and spherical bearings are used around the world in:

- Business machines
- Food processing equipment
- Small conveyors
- Lawn mowers and snow blowers
- HVAC
- Farm tractors and harvesting equipment
- Defense vehicles
- Class 8 trucks

PRODUCT SPECIFICATIONS

Bore Tolerances Chart

Units	Bore Size	Lubrication	Mean	Tolerance
Steel & Cast Iron Bronze Bushed Balls	0" - 15/16" 1 - up 0 - 15/16 1 - up	Oil-Plastic E Oil-Plastic E Grease Grease	+.001 +.0015 +.0015 +.0025	+.0005 - +.0015 +.001 - +.0027 +.001 - +.002 +.002 - +.0037
Plain Cast Iron Balls	0" - 1-1/4" 1 - 15/16 up	Grease Grease	+.0025 +.003	+.005 - +.003 +.003 - +.004
Nylon Balls	All Sizes	None	+.006	+.004 - +.008

BEARING MATERIAL

- Aluminum
- Brass
- Delrin
- Nylon
- Oil Impregnated Bronze
- Oil Impregnated Iron
- Stainless Steel
- Steel
- Wood





150 Libbey Ave Oshkosh WI 54901 P (920) 235–3710 F (920) 235–4523 sales@triangleoshkosh.com www.triangleoshkosh.com

NYLON

Diameter	Length	Bore Sizes	1/4"	5/16"	3/8"	7/16"	1/2"	5/8"	3/4"
1.00"	.50"		N4	N5	N6	N7	N8	N10	N12
1.19	.75								M12

SINTERED BRONZE

Diameter	Length	Bore Sizes	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1.00"	.50"		1406P	1408P	1410P			
1.19	.75			B8	B10	B12	B14	
1.50	1.00							4016P

B Series and 4016P are also available with grease fittings.

SINTERED IRON

Diameter	Length	Bore Sizes	1/2"	5/8"	3/4"	7/8"	1"
1.00"	.50"		1508P	1510P	1512P		
1.19	.75		W8	W10	W12	W14	
1.50	1.00					4214P	4216P
1.69	1.25						4316P

4214P, 4216P and 4316P are also available with grease fittings.

CAST IRON

Diameter	Length	Bore 9 1/2"		3/4"	7/8"	1"				
1.69"	1.25"	J8G	J10G	J12G	J14G	J16G				
		1- 1/16"	1- 1/8"	1- 3/16"	1- 1/4"	_	_	1- 1/2"	1- 5/8"	1- 3/4"
2.00	1.50	K17G	K18G	K19G	K20G	K22G				
2.00	1.50		T18G	T19G	T20G					
2.25	1.75	L17G	L18G	L19G	L20G	L22G	L23G	L24G	L26G	L28G
2.25	1.75		U18G	U19G	U20G		U24G			

J Series is also available with 3/16" and 15/16" bore.

L Series is also available with 15/16" bore.

BRONZED BUSHED

Diameter	Length	Sizes 5/8"	3/4"	7/8"	1"	1- 1/8"	1- 3/16"	_	_
2.00"	1.50"					T18G	T19G	T20G	
2.25	1.75					U18G	U19G	U20G	U24G

T Series also is available with 3/16" and 15/16" bore.