



|                      |             |
|----------------------|-------------|
| Bore Diameter (d)    | 30 mm       |
| Outside Diameter (D) | 55 mm       |
| Width (B)            | 32 mm       |
| Width (C)            | 16 mm       |
| Dynamic Load AxialCA | 3529.5 lbs  |
| Static Load Axial ca | 8655.14 lbs |
| Brand                | FAG         |

|           |                                |
|-----------|--------------------------------|
| COMPONENT | Axial Angular Contact Bearings |
|-----------|--------------------------------|



Pacific International Bearing, Inc.  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

|   |        |
|---|--------|
| <b>234406-M-SP</b><br>FAG<br>30mm X 55mm X 32mm, Axial Angular Contact, Ball Bearing, Double Direction, Seperable, Restricted Tolerance | UNIT   |
|   | Metric |
|   | SHEET  |