




Bore Diameter (d)	30 mm
O.D. (D)	72 mm
Width (B)	19 mm
Closure	Rubber Seal Non-Contact
Brand	TPI
Precision	Abec 1
Radial Clearance	C3
Lubrication	L627 Polyrex EM Grease
Dynamic Load(Cr)	6002.40 lbs
Static Load Cap (C0r)	3372.13 lbs
Ball Material	52100 Chrome Steel
Ring Material	52100 Chrome Steel
Series	6306



Non-contact sealed type (LLB)

COMPONENT	METRIC SERIES SEALED	
2TS3-6306C3 TPI 30 Mm X 72 Mm X 19 Mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Non-contact Rubber Seals	UNIT	
	Metric	
	SHEET	



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.