



| | |
|----------------------|---------------------|
| Bore Diameter (d) | 15 mm |
| Outside Diameter (D) | 35 mm |
| Width (B) | 15.9 mm |
| Contact Angle | 30° contact angle |
| Brand | FAG |
| Ring Material | Chrome Steel 100Cr6 |
| Ball Material | 52100 Chrome Steel |
| Dynamic Load(Cr) | 2832.59 lbs |
| Static Load(C0r) | 1663.59 lbs |
| Closure | Metallic Shield |

| | |
|-----------|------------------------------------|
| COMPONENT | Double Row Angular Contact Bearing |
|-----------|------------------------------------|



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

3202-BD-XL-2Z-C3
FAG
 15mm X 35mm X 15.9mm, Double Row Angular Contact, Angular Contact Ball Bearing, Double Row / Shields, -bd-xl-2z

| |
|--------|
| UNIT |
| METRIC |
| SHEET |