

		$D = \begin{pmatrix} a \\ c \\$			
	17 mm	<u> </u>			
	40 mm	_	В		
	17.5 mm				
	30° contact angle	_			
	FAG	_			
	Chrome Steel 100Cr6	_			
	52100 Chrome Steel				
	3484.54 lbs				
	2135.68 lbs		COMPONENT	Double Row Angula	r Contact
	Rubber Seal			Bearing	
Decific International Rearing Inc.		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	3203-BD-	XL-2HRS	UNIT
	33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	FA 17mm X 40mm X 17 Angular Contact A	.5mm, Double Row	METRIC
www.pibsales.com		for the use of the file, information or specifications.	Angular Contact, Angular Contact Ball Bearing, Double Row / Seals, -bd-xl-2hrs		SHEET

Bore Diameter (d)	17 mm		
Outside Diameter (D)	40 mm		
Width (B)	17.5 mm		
Contact Angle	30° contact angle		
Brand	FAG		
Ring Material	Chrome Steel 100Cr6		
Ball Material	52100 Chrome Steel		
Dynamic Load(Cr)	3484.54 lbs		
Static Load(C0r)	2135.68 lbs		
Closure	Rubber Seal		