

Width (B)

Brand

Closure

0.D. (D)

Contact Angle

Ring Material

Ball Material

Dynamic Load(Cr)

Bore Diameter (d)

Static Load Cap (COr)

		$D = \begin{bmatrix} a \\ c \\$			
	20.6 mm				
30° contact angle B					
	FAG				
Chrome Steel 100Cr6					
52100 Chrome Steel					
	4631.06 lbs				
Rubber Seal					
	20 mm				
	2900.04 lbs		COMPONENT	Double Row Angular Contact Bearing	
	47 mm				
Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	3204-BD-XL-2HRS-TVH- C3 FAG 20mm X 47mm X 20.6mm, Double Row Angular Contact, Angular Contact Ball Bearing, Double Row / Seals, -bd-xl-2hrs- tvh		UNIT
					METRIC
					SHEET