

			$D = \begin{bmatrix} a \\ c \\$				
		30 mm	· · · · · · · · · · · · · · · · · · ·				
		62 mm	В				
		23.8 mm					
		30° contact angle					
		FAG					
		Chrome Steel 100Cr6					
		52100 Chrome Steel					
		6969.08 lbs					
		4990.76 lbs		COMPONENT	Double Row Angula	r Contact	
		Rubber Seal			Bearing		
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	3206-BD-X	L-2HRS-C3	UNIT	
				FA 30mm X 62mm X 23 Angular Contact, Ai	.8mm, Double Row	METRIC	
www.pibsal		www.pibsales.com		Bearing, Double Row	•	SHEET	

Bore Diameter (d)	30 mm
Outside Diameter (D)	62 mm
Width (B)	23.8 mm
Contact Angle	30° contact angle
Brand	FAG
Ring Material	Chrome Steel 100Cr6
Ball Material	52100 Chrome Steel
Dynamic Load(Cr)	6969.08 lbs
Static Load(C0r)	4990.76 lbs
Closure	Rubber Seal