

			$D = \begin{bmatrix} a \\ c \\$				
40 mm							
		80 mm	В				
		30.2 mm					
		30° contact angle					
		FAG					
		Chrome Steel 100Cr6					
		52100 Chrome Steel					
		11465.26 lbs					
		8542.74 lbs		COMPONENT Double Row Angular Contact		r Contact	
		Rubber Seal			Bearing		
Pacific International Bearing, Inc.		nternational Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	3208-BD-XL-2HRS		UNIT	
	33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com			FA 40mm X 80mm X 30 Angular Contact, Ai	.2mm, Double Row	METRIC	
www.pibsales.com		www.pibsales.com		Bearing, Double Row	•	SHEET	

Bore Diameter (d)	40 mm		
Outside Diameter (D)	80 mm		
Width (B)	30.2 mm		
Contact Angle	30° contact angle		
Brand	FAG		
Ring Material	Chrome Steel 100Cr6		
Ball Material	52100 Chrome Steel		
Dynamic Load(Cr)	11465.26 lbs		
Static Load(C0r)	8542.74 lbs		
Closure	Rubber Seal		