

| | | $D = \begin{pmatrix} a \\ c \\$ | | | |
|--|-------------------------------------|--|--|---|-----------|
| | 30.2 mm | • | | <u>I</u> | |
| | 30° contact angle | | B | | |
| | FAG | | | | |
| | Chrome Steel 100Cr6 | | | | |
| | 52100 Chrome Steel | | | | |
| | 11240.45 lbs | | | | |
| | Rubber Seal | | | | |
| | 45 mm | | | | |
|) | 8767.55 lbs | | COMPONENT | Double Row Angula | r Contact |
| | 85 mm | | | Bearing | |
| | Pacific International Bearing, Inc. | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB | 3209-BD-XL-2HRS-TVH | | UNIT |
| 33258 Central Ave, Union City, CA 9458 1-800-228-8895, 510-512-7000, info@pibsales.com | | makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or | 45mm X 85mm X 30 Angular Contact, A | .2mm, Double Row Igular Contact Ball | METRIC |
| | www.pibsales.com | specifications. You are solely responsible for the use of the file, information or specifications. | Bearing, Double Row / Seals, -bd- xl-2hrs-tvh | | SHEET |

| Width (B) | 30.2 mm | | |
|-----------------------|---------------------|--|--|
| Contact Angle | 30° contact angle | | |
| Brand | FAG | | |
| Ring Material | Chrome Steel 100Cr6 | | |
| Ball Material | 52100 Chrome Steel | | |
| Dynamic Load(Cr) | 11240.45 lbs | | |
| Closure | Rubber Seal | | |
| Bore Diameter (d) | 45 mm | | |
| Static Load Cap (C0r) | 8767.55 lbs | | |
| 0.D. (D) | 85 mm | | |
| | | | |