

		$D = \begin{bmatrix} a \\ c \\$				
	65 mm					
	120 mm	_	B			
	38.1 mm					
	30° contact angle					
	FAG	_				
	Chrome Steel 100Cr6	_				
	52100 Chrome Steel	_				
	19333.57 lbs					
	17310.29 lbs		COMPONENT	Double Row Angula	r Contact	
	Rubber Seal			Bearing	Bearing	
And specificat		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	3213-BD-XI	-2HRS-C3	UNIT	
	33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	FA 65mm X 120mm X 3 Angular Contact A	8.1mm, Double Row	METRIC	
www.pibsales.com		specifications. You are solely responsible for the use of the file, information or specifications.	Angular Contact, Angular Contact Ball Bearing, Double Row / Seals, -bd-xl-2hrs		SHEET	

Bore Diameter (d)	65 mm		
	0511111		
Outside Diameter (D)	120 mm		
Width (B)	38.1 mm		
Contact Angle	30° contact angle		
Brand	FAG		
Ring Material Ball Material	Chrome Steel 100Cr6		
	52100 Chrome Steel		
Dynamic Load(Cr)	19333.57 lbs		
Static Load(C0r)	17310.29 lbs		
Closure	Rubber Seal		