

			$D = \begin{pmatrix} a \\ c \\$			
	25 mm					
)	62 mm			В		
	25.4 mm					
30° contact angle						
FAG		-				
Chrome Steel 100Cr6		-				
52100 Chrome Steel						
	7081.48 lbs					
4720.99 lbs				COMPONENT Double Row Angular Contact		r Contact
Metallic Shield			Bearing			
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	FAG 25mm X 62mm X 25.4mm, Double Row Angular Contact, Angular Contact Ball Bearing, Double Row / Shields, -bd-xl-2z-		UNIT
			makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or			METRIC
						SHEET

Bore Diameter (d)	25 mm		
Outside Diameter (D)	62 mm		
Width (B)	25.4 mm		
Contact Angle	30° contact angle		
Brand	FAG		
Ring Material	Chrome Steel 100Cr6		
Ball Material	52100 Chrome Steel		
Dynamic Load(Cr)	7081.48 lbs		
Static Load(C0r)	4720.99 lbs		
Closure	Metallic Shield		