

|  | COMPONENT   | Double Row Angula<br>Bearing | ar Contact |
|--|---|------------------------------|------------|
| This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB | Angular Contact, Angular Contact Ball<br>Bearing Double Row (Steel Cage |                              | UNIT       |
| makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or |   |                              | METRIC     |
| specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.   |   |                              | SHEET      |

| Bore Diameter (d)    | 70 mm               |
|----------------------|---------------------|
| Outside Diameter (D) | 150 mm              |
| Width (B)            | 63.5 mm             |
| Contact Angle        | 30° contact angle   |
| Brand                | FAG                 |
| Ring Material        | Chrome Steel 100Cr6 |
| Ball Material        | 52100 Chrome Steel  |
| Dynamic Load(Cr)     | 38667.14 lbs        |
| Static Load(C0r)     | 30349.21lbs         |
| Closure              | Open                |
|                      |                     |

Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com