

70 mm							
)	150 mm			B			
	63.5 mm						
	45° contac	45° contact angle					
	FAG						
	Chrome St	eel100Cr6					
	52100 Chro	ome Steel					
	35295 lbs						
	35295 lbs			COMPONENT	Double Row Angular Contact		
	Open]	Bearing			
Pacific International Bearing, Inc.		nal Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB	ifications are provided for and evaluation purposes only, 3314–DA		UNIT	
	33258 Central Ave, U 1-800-228-8895 info@pibsa	nion City, CA 94587 , 510-512-7000, ales.com	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	70mm X 150mm X 6	AG 3.5mm, Double Row ngular Contact Ball	METRIC	
	www.pibsa	ales.com	specifications. You are solely responsible for the use of the file, information or specifications.	Bearing, Double Row / Split Inner Ring		SHEET	

Bore Diameter (d)	70 mm
Outside Diameter (D)	150 mm
Width (B)	63.5 mm
Contact Angle	45° contact angle
Brand	FAG
Ring Material	Chrome Steel 100Cr6
Ball Material	52100 Chrome Steel
Dynamic Load(Cr)	35295 lbs
Static Load(C0r)	35295 lbs
Closure	Open