

		D	$D = \begin{bmatrix} a \\ c \\$		
	25 mm				
	37 mm		В		
	10 mm				
	25° contact angle				
	INA				
	Chrome Steel 100Cr6				
	52100 Chrome Steel				
	1326.37 lbs				
	1236.45 lbs		COMPONENT	Double Row Angular Contact	
	Rubber Seal			Bearing	
	Pacific International Bearing, Inc.	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice PIB	pecifications are provided for nce and evaluation purposes only, subject to change without notice. PIB is no representations, warranties or ntees as to the appropriateness, acy, completeness, or suitability for		
	33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com	hion City, CA 94587 510-512-7000, ales.com INA INA S10-512-7000, ales.com INA S10-512-7000, accuracy, completeness, or suitability for any purpose, of the file, information or INA S10-512-7000, S10-512-700, S10-512-700, S10-512-700, S10-512-700, S10-512-700, S10-512-700, S10-512-700, S10-512-700, S1			
www.pibsales.com		specifications. You are solely responsible for the use of the file, information or specifications.	Bearing, Double Row / Seals, -b-2rs-tvh		SHEET

Bore Diameter (d)	25 mm37 mm10 mm25° contact angleINAChrome Steel 100Cr652100 Chrome Steel1326.37 lbs1236.45 lbsRubber Seal		
Outside Diameter (D)			
Width (B)			
Contact Angle			
Brand			
Ring Material			
Ball Material			
Dynamic Load(Cr)			
Static Load(C0r)			
Closure			