|   |                                       | D  | d   | $d_1 \\ d_2 D_2$ |                |
|---|---------------------------------------|--|---|------------------|----------------|
| Bore Diameter (d) 15 mm   |                                       | $\partial \overline{d} = \overline{1} - \overline{1} \overline{1} \overline{1} \overline{1} \overline{1}$  |   |                  |                |
| Outside Diameter (D)  | 32 mm                                 |  |   |                  |                |
| Width (B)   | 9 mm                                  |  |   |                  |                |
| Closure   | Rubber Seal Contact                   |  |   |                  |                |
| Ring Material   | 52100 Chrome Steel                    |  |   |                  |                |
| Ball Material   | 52100 Chrome Steel                    |  |   |                  |                |
| Brand   | FAG                                   |  |   |                  |                |
| Radial Clearance  | C3                                    | ]  |   |                  |                |
| Series  | 6002                                  |  | COMPONENT   | METRIC SERIES S  | SEALED         |
| Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000, |                                       | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for | 6002–C–2HRS–C3<br>FAG<br>15 Mm X 32 Mm X 9 Mm, Single Row Radial, |                  | UNIT<br>METRIC |
|   | info@pibsales.com<br>www.pibsales.com | any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications  | Deep Groove Ball Bearing, Two Contact<br>Rubber Seals             |                  | SHEET          |

specifications.