| P | B | D | d | d ₁ d ₂ D ₂ | |
|---|------------------------------------|--|---|---|--------|
| Bore Diameter (d) 50 mm | | | ▼ | | |
| Outside Diameter (D) | 80 mm | | | | |
| Width (B) | 16 mm | | | | |
| Closure | Rubber Seal Non-Contact | | | | |
| Ring Material | 52100 Chrome Steel | | | | |
| Ball Material | 52100 Chrome Steel | | | | |
| Brand | FAG | | | | |
| Radial Clearance | C3 | 7 | | | |
| Lubrication | L252 Grease 250 GR | 7 | | | |
| Series | 6010 | | COMPONENT | METRIC SERIES | SEALED |
| | acific International Bearing, Inc. | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB | 6010-2RSR-L252-C3 | | UNIT |
| 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com | | makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or | FAG 50 Mm X 80 Mm X 16 Mm, Single Row Radial, Deep Groove Ball Bearing, Two Non Contact Rubber Seals | | METRIC |
| | | specifications. You are solely responsible for the use of the file, information or specifications. | | | SHEET |