$ \begin{array}{c} & & \\ & & & \\ & $					
Bore Diameter (d)	17 mm				
Outside Diameter (D)	40 mm				
Width (B)	12 mm				
Closure	Rubber Seal Non-Contact				
Ring Material	52100 Chrome Steel				
Ball Material	52100 Chrome Steel				
Brand	FAG				
Precision	Abec 3				
Radial Clearance	Normal				
Lubrication	L038 Mobil Polyrex EM Grease				
Dynamic Load(Cr) 2135.69 lbs					
Static Load(C0r)	1067.84 lbs				
Series	6203		COMPONENT	METRIC SERIES S	SEALED
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	F/	SR F.A.G. AG 12 Mm, Single Row	UNIT
			Radial, Deep Groov	e Ball Bearing, Two Rubber Seals	SHEET