



|                      |                              |
|----------------------|------------------------------|
| Bore Diameter (d)    | 17 mm                        |
| Outside Diameter (D) | 40 mm                        |
| Width (B)            | 12 mm                        |
| Closure              | Metallic Shield              |
| Ring Material        | 52100 Chrome Steel           |
| Ball Material        | 52100 Chrome Steel           |
| Brand                | FAG                          |
| Precision            | Abec 3                       |
| Radial Clearance     | C3                           |
| Lubrication          | L038 Mobil Polyrex EM Grease |
| Dynamic Load(Cr)     | 2135.69 lbs                  |
| Static Load(C0r)     | 1067.84 lbs                  |
| Series               | 6203                         |

|           |                        |
|-----------|------------------------|
| COMPONENT | Metric Series Shielded |
|-----------|------------------------|



Pacific International Bearing, Inc.  
 33258 Central Ave. Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

|  |        |
|--|--------|
| <b>6203.2ZR.C3 FAG</b><br>FAG<br>17 Mm X 40 Mm X 12 Mm, Single Row<br>Radial, Deep Groove Ball Bearing, Two<br>Metal Shields | UNIT   |
|  | METRIC |
|  | SHEET  |