



Bore Diameter (d)	20 mm
O.D. (D)	47 mm
Width (B)	14 mm
Closure	Metallic Shield
Brand	FAG
Precision	Abec 3
Radial Clearance	C3
Lubrication	L038 Mobil Polyrex EM Grease
Dynamic Load(Cr)	2855.07 lbs
Static Load Cap (C0r)	1472.50 lbs
Ball Material	52100 Chrome Steel
Ring Material	52100 Chrome Steel
Series	6204

COMPONENT	Metric Series Shielded
-----------	------------------------



Pacific International Bearing, Inc.  
 33258 Central Ave. Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
 info@pibsales.com  
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**6204.2ZR.C3 FAG**  
**FAG**  
 20 Mm X 47 Mm X 14 Mm, Single Row  
 Radial, Deep Groove Ball Bearing, Two  
 Metal Shields

UNIT
METRIC
SHEET