Dd	B	$D \qquad \qquad$			
Bore Diameter (d)	25 mm				
Outside Diameter (D)	52 mm				
Width (B)	15 mm				
Closure	Metallic Shield				
Ring Material	52100 Chrome Steel				
Ball Material	52100 Chrome Steel				
Brand	FAG				
Precision	Abec 3				
Radial Clearance	С3				
Lubrication	L038 Mobil Polyrex EM Grease				
Dynamic Load(Cr)	3147.33 lbs				
Static Load(C0r)	1753.51 lbs				
Series	6205	]	COMPONENT	Metric Series S	hielded
PIB	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or	<b>6205.2ZR.C3</b> FAG 25 Mm X 52 Mm X 15 Mm, Single Row Radial, Deep Groove Ball Bearing, Two Metal Shields		UNIT METRIC
		specifications. You are solely responsible for the use of the file, information or specifications.			SHEET

Г