| $\left  \begin{array}{c} \hline \\ \hline $ |  |  |  |                 |        |
|---|--|--|--|-----------------|--------|
| Bore Diameter (d) 35 mm   |  |  |  |                 |        |
| Outside Diameter (D) 72 mm  |  |  |  |                 |        |
| Width (B)   | 17 mm  |  |  |                 |        |
| Closure   | Rubber Seal Non-Contact  |  |  |                 |        |
| Ring Material   | 52100 Chrome Steel   | B  |  |                 |        |
| Ball Material   | 52100 Chrome Steel   |  |  |                 |        |
| Brand   | FAG  |  |  |                 |        |
| Radial Clearance  | C3   |  |  |                 |        |
| Lubrication   | L038 Mobil Polyrex EM Grease   | ]  |  |                 |        |
| Series  | 6207   | ]  | COMPONENT  | METRIC SERIES S | SEALED |
| PIB   | Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications. | 62U7-C-2BRS-LU38-C3<br>FAG<br>35 Mm X 72 Mm X 17 Mm, Single Row<br>Radial, Deep Groove Ball Bearing, Two |                 | UNIT   |
|   |  |  |  |                 | METRIC |
|   |  |  |  |                 | SHEET  |